

CDM4161 - Pre-calibrated module for carbon dioxide


Features:

- * High selectivity to CO₂
- * Maintenance free
- * Low power consumption
- * Long life
- * Compact size
- * Pre-calibrated
- * Low cost

CDM4161 is a new unit which uses TGS4161, Figaro's low-power consumption solid electrolyte CO₂ sensor. Due to Figaro's proprietary idea for signal processing with a microcomputer, no maintenance is required for this module. By application of DC voltage to the module, an analog output voltage proportional to CO₂ concentration can be obtained. The module can generate a control signal based on a user-selectable threshold concentration. When compared with traditional CO₂ sensor modules using IR sensors, Figaro's CO₂ module is much more cost effective, making this module the ideal choice for indoor air quality control systems.

Applications:

- * Indoor air quality control
- * CO₂ monitors



CDM4161 dimensions

| Pin No. | Name | Description |
|---------|-------|--------------------------------------|
| 1 | VIN | Power supply input |
| 2 | VCONC | CO ₂ concentration output |
| 3 | CTRL | Control signal output |
| 4 | TRBL | Trouble signal output |
| 5 | GND | Common ground |

CDM4161 pin designations of CN1

NOTE: CN1 should be MB5P-90S, mfg. by JST.

Recommended receptacle for connector: 05JQ-BT, mfg. by JST.

Specifications:

| | | |
|---|---|--|
| Product name | Carbon dioxide (CO ₂) sensor module | |
| Model No. | CDM4161-L00 | CDM4161-M00 |
| Detection range | 400 to 4,000ppm | 400 to 8,000ppm |
| Sensor (principle) | TGS4161 (solid state electrolyte) | |
| Accuracy (*1) | approx. ±20% full scale | |
| Power supply | DC5.0±0.2V regulated | |
| Power consumption | 300mW (Max) | |
| Operational temperature & humidity range | -10°~+50°C, 5~95%RH (avoid condensation) | |
| Storage temperature & humidity range | -20°~+60°C, 5~90%RH (pack in a moisture proof bag) | |
| Warm up time | 2 hours | |
| CO ₂ concentration signal (*2) | Continuous analog output proportional to CO ₂ concentration | |
| | Vconc = CO ₂ concentration/1,000 (DC 4V full scale) | Vconc = CO ₂ concentration/2,000 (DC 4V full scale) |
| Control signal | ON: HIGH output (when CO ₂ conc. exceeds threshold) OFF: LOW output | |
| | 800/ 1,000/ 1,500/ 2,000 (ppm) | 1,000/ 2,000/ 5,000/ 8,000 (ppm) |
| Malfunction signal | ON: LOW output (sensor malfunction) OFF: FLOAT NC | |
| LED display | Green LED: Lights while power is on (blinks during warm up) | |
| | Yellow LED: Blinks during trouble | |
| | Red LED: Lights when CO ₂ concentration exceeds the threshold | |
| Reset switch | Establishes the ambient CO ₂ concentration as 400ppm when pushed | |
| Dimensions | 45 x 60 x 19mm (45 x 67 x 19mm incl. CN1) | |
| Weight | approx. 17g | |

Note 1: Assumes benchmark is set accurately at 400ppm of CO₂. This value does not contain long term drift.

Note 2: In this module, the CO₂ concentration is calculated by measuring the relative change of sensor output at the measuring point from sensor output in clean air (assumed to be 400ppm of CO₂).

IMPORTANT: This product is not designed and authorized for use as a critical component in life support applications wherein a failure or malfunction of the products may result in injury or threat to life. Figaro Engineering Inc. reserves the right to make changes without notice to this product to improve reliability, functioning or design.