

TOSHIBA Bipolar Digital Integrated Circuit Silicon Monolithic

**ULN2803APG,ULN2803AFWG,ULN2804APG,ULN2804AFWG
(Manufactured by Toshiba Malaysia)****8ch Darlington Sink Driver**

The ULN2803APG / AFWG Series are high-voltage, high-current darlington drivers comprised of eight NPN darlington pairs.


All units feature integral clamp diodes for switching inductive loads.

Applications include relay, hammer, lamp and display (LED) drivers.

The suffix (G) appended to the part number represents a Lead (Pb)-Free product.

Features


- Output current (single output)
500 mA (Max.)
- High sustaining voltage output
50 V (Min.)
- Output clamp diodes
- Inputs compatible with various types of logic.
- Package Type-APG : DIP-18pin
- Package Type-AFWG : SOL-18pin



Weight
DIP18-P-300-2.54F: 1.478 g (Typ.)
SOL18-P-300-1.27 : 0.48 g (Typ.)


Pin Connection (top view)

Type	Input Base Resistor	Designation
ULN2803APG / AFWG	2.7 kΩ	TTL, 5 V CMOS
ULN2804APG / AFWG	10.5 kΩ	6~15 V PMOS, CMOS




Schematics (each driver)

ULN2803APG / AFWG



ULN2804APG / AFWG



Note: The input and output parasitic diodes cannot be used as clamp diodes.

Absolute Maximum Ratings (Ta = 25°C)

Characteristic		Symbol	Rating	Unit
Output sustaining voltage		V _{CE} (SUS)	-0.5~50	V
Output current		I _{OUT}	500	mA / ch
Input voltage		V _{IN}	-0.5~30	V
Clamp diode reverse voltage		V _R	50	V
Clamp diode forward current		I _F	500	mA
Power dissipation	APG	P _D	1.47	W
	AFWG		0.92 / 1.31 (Note)	
Operating temperature		T _{opr}	-40~85	°C
Storage temperature		T _{stg}	-55~150	°C

Note: On Glass Epoxy PCB (75 × 114 × 1.6 mm Cu 20%)

Recommended Operating Conditions (Ta = -40~85°C)

Characteristic		Symbol	Test Condition	Min	Typ.	Max	Unit	
Output sustaining voltage		V _{CE} (SUS)		0	—	50	V	
Output current	APG	I _{OUT}	T _{pw} = 25 ms, Duty = 10%, 8 Circuits	0	—	347	mA / ch	
			T _{pw} = 25 ms, Duty = 50%, 8 Circuits	0	—	123		
	AFWG		T _{pw} = 25 ms, Duty = 10%, 8 Circuits	0	—	268		
			T _{pw} = 25 ms, Duty = 50%, 8 Circuits	0	—	90		
Input voltage		V _{IN}		0	—	30	V	
Input voltage (Output on)	ULN2803A	V _{IN} (ON)		3.5	—	30	V	
	ULN2804A			8	—	30		
Clamp diode reverse voltage		V _R		—	—	50	V	
Clamp diode forward current		I _F		—	—	400	mA	
Power dissipation	APG	P _D	T _a = 85°C	—	—	0.76	W	
	AFWG		T _a = 85°C (Note)	—	—	0.48		

Note: On Glass Epoxy PCB (75 x 114 x 1.6 mm Cu 20%)


Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Characteristic	Symbol	Test Cir-Cuit	Test Condition		Min	Typ.	Max	Unit			
Output leakage current ULN2804A	I_{CEX}	1	$V_{CE} = 50 \text{ V}$	$T_a = 25^\circ\text{C}$	—	—	50	μA			
			$V_{CE} = 50 \text{ V}$	$T_a = 85^\circ\text{C}$	—	—	100				
			$V_{CE} = 50 \text{ V}$	$V_{IN} = 1 \text{ V}$	—	—	500				
Collector-emitter saturation voltage		V _{CE} (sat)	2	$I_{OUT} = 350 \text{ mA}, I_{IN} = 500 \mu\text{A}$	—	1.3	1.6	V			
				$I_{OUT} = 200 \text{ mA}, I_{IN} = 350 \mu\text{A}$	—	1.1	1.3				
				$I_{OUT} = 100 \text{ mA}, I_{IN} = 250 \mu\text{A}$	—	0.9	1.1				
Input current	ULN2803A	I_{IN} (ON)	2	$V_{IN} = 3.85 \text{ V}$	—	0.93	1.35	mA			
	ULN2804A			$V_{IN} = 5 \text{ V}$	—	0.35	0.5				
				$V_{IN} = 12 \text{ V}$	—	1.0	1.45				
		I_{IN} (OFF)	4	$I_{OUT} = 500 \mu\text{A}, T_a = 85^\circ\text{C}$	50	65	—	μA			
Input voltage (Output on)	ULN2803A	V _{IN} (ON)	5	$V_{CE} = 2 \text{ V}, I_{OUT} = 200 \text{ mA}$	—	—	2.4	V			
				$V_{CE} = 2 \text{ V}, I_{OUT} = 250 \text{ mA}$	—	—	2.7				
				$V_{CE} = 2 \text{ V}, I_{OUT} = 300 \text{ mA}$	—	—	3.0				
	ULN2804A			$V_{CE} = 2 \text{ V}, I_{OUT} = 125 \text{ mA}$	—	—	5.0				
				$V_{CE} = 2 \text{ V}, I_{OUT} = 200 \text{ mA}$	—	—	6.0				
				$V_{CE} = 2 \text{ V}, I_{OUT} = 275 \text{ mA}$	—	—	7.0				
				$V_{CE} = 2 \text{ V}, I_{OUT} = 350 \text{ mA}$	—	—	8.0				
DC current transfer ratio	h_{FE}	2	$V_{CE} = 2 \text{ V}, I_{OUT} = 350 \text{ mA}$		1000	—	—				
Clamp diode reverse current	I_R	6	$T_a = 25^\circ\text{C}$ (Note)		—	—	50	μA			
			$T_a = 85^\circ\text{C}$ (Note)		—	—	100				
Clamp diode forward voltage	V_F	7	$I_F = 350 \text{ mA}$		—	—	2.0	V			
Input capacitance	C_{IN}	—			—	15	—	pF			
Turn-on delay	t_{ON}	8	$R_L = 125 \Omega, V_{OUT} = 50 \text{ V}$		—	0.1	—	μs			
Turn-off delay	t_{OFF}		$R_L = 125 \Omega, V_{OUT} = 50 \text{ V}$		—	0.2	—				


Note: $V_R = V_R \text{ MAX.}$

Test Circuit


1. I_{CEX}




2. $V_{CE}(\text{sat}), h_{FE}$




3. $I_{IN}(\text{ON})$




4. $I_{IN}(\text{OFF})$




5. $V_{IN}(\text{ON})$




6. I_R



7. V_F



8. t_{ON} , t_{OFF}



Note 1: Pulse Width 50 μs , Duty Cycle 10%

Output Impedance 50 Ω , $t_r \leq 5 \text{ ns}$, $t_f \leq 10 \text{ ns}$

Note 2: See below.

Input Condition

Type Number	R_1	V_{IH}
ULN2803A	0 Ω	3 V
ULN2804A	0 Ω	8 V







Note 3: C_L includes probe and jig capacitance


Precautions for Using

This IC does not integrate protection circuits such as overcurrent and overvoltage protectors.

Thus, if excess current or voltage is applied to the IC, the IC may be damaged. Please design the IC so that excess current or voltage will not be applied to the IC.

Utmost care is necessary in the design of the output line, COMMON and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.






Package Dimensions

DIP18-P-300-2.54F

Unit: mm




Weight: 1.478 g (Typ.)

Package Dimensions

SOL18-P-300-1.27

Unit: mm



Weight: 0.48 g (Typ.)